

### VACUFLEX® VSM AS

Very smooth inside profile hose made of antistatic modified TPO

- Applications** vacuum cleaner, industrial vacuum cleaners, cleaning, grinding machines, textile fiber extraction
- Structure** TPO, black, opaque, profile helix / solid profile helix
- Temperature** -50°C up to 60°C
- Properties** smooth inside, corrugated outside, excellent flexibility, permanently antistatic, very good resilience when pressed or twisted



Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
20	28,00	50	0,60	0,60	0,19240	4-1806-020-00
25	33,00	50	0,60	0,60	0,24000	4-1806-025-00
27	35,50	60	0,60	0,60	0,25630	4-1806-027-00
28	36,00	60	0,60	0,60	0,28550	4-1806-028-00
29	37,00	70	0,50	0,50	0,29610	4-1806-029-00
32	40,50	70	0,50	0,50	0,30860	4-1806-032-00
35	43,60	75	0,50	0,50	0,33492	4-1806-035-00
36	43,00	75	0,50	0,50	0,34605	4-1806-036-00
38	48,00	80	0,40	0,40	0,36882	4-1806-038-00
40	50,00	90	0,40	0,40	0,38231	4-1806-040-00
45	55,00	100	0,30	0,30	0,43073	4-1806-045-00
48	58,00	110	0,28	0,28	0,44886	4-1806-048-00
50	61,00	120	0,25	0,25	0,46810	4-1806-050-00
60	72,00	140	0,20	0,20	0,57903	4-1806-060-00
63	74,00	150	0,18	0,18	0,60519	4-1806-063-00
70	81,00	165	0,17	0,17	0,73000	4-1806-070-00
75	87,00	180	0,16	0,16	0,55100	4-1806-075-00
80	92,00	200	0,15	0,15	0,93646	4-1806-080-00