

VACUFLEX® K1Z-MS PU MHR

Flexible spiral hose with a smooth inner surface, made of polyester-polyurethane

- Applications** extraction systems, extractions arms, ventilation, venting, vehicle construction
- Structure** TPU / Polyether-Polyurethane, uncolored, transparent, steel wire / spring steel wire / not coated / copper plated
- Temperature** -40°C up to 90°C, short term up to 125°C
- Properties** medium weight, good flexibility, corrugated outside, good tensile strength ultimate elongation, hydrolysis & microbe resistant, good ozone- & UV-resistance, weather proof, rot proof



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
35	41,00	0,80	41	2,30	0,55	0,27300	6-2000-035-00/998
38	44,00	0,80	44	2,30	0,55	0,29500	6-2000-038-00/998
42	48,00	0,80	48	2,30	0,55	0,32500	6-2000-042-00/998
45	51,00	0,80	51	2,30	0,55	0,34700	6-2000-045-00/998
50	56,00	0,80	56	2,30	0,55	0,38400	6-2000-050-00/998
55	61,00	0,80	61	2,00	0,42	0,42100	6-2000-055-00/998
60	66,00	0,80	66	2,00	0,42	0,45900	6-2000-060-00/998
65	71,00	0,80	71	2,00	0,42	0,49600	6-2000-065-00/998
70	76,00	0,80	76	2,00	0,42	0,51800	6-2000-070-00/998
76	82,00	0,80	82	1,50	0,35	0,57700	6-2000-076-00/998
80	86,00	0,80	86	1,50	0,35	0,59100	6-2000-080-00/998
83	89,00	0,80	89	1,50	0,35	0,61300	6-2000-083-00/998
100	107,00	0,80	107	1,00	0,30	0,86800	6-2000-100-00/998
120	127,00	0,80	127	1,00	0,30	1,06200	6-2000-120-00/998
125	132,00	0,80	132	1,00	0,30	1,08200	6-2000-125-00/998
130	137,00	0,80	137	1,00	0,30	1,12400	6-2000-130-00/998
140	147,00	0,80	147	1,00	0,30	1,21000	6-2000-140-00/998
150	157,00	0,80	157	0,70	0,25	1,29500	6-2000-150-00/998
160	167,00	0,80	167	0,70	0,25	1,38000	6-2000-160-00/998
175	182,00	0,80	182	0,70	0,25	1,50800	6-2000-175-00/998
180	187,00	0,80	187	0,70	0,25	1,55100	6-2000-180-00/998
200	207,00	0,80	207	0,70	0,25	1,74700	6-2000-200-00/998

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
203	210,00	0,80	210	0,70	0,25	1,93400	6-2000-203-00/998
225	232,00	0,80	232	0,70	0,25	2,35300	6-2000-225-00/998
250	257,00	0,80	257	0,50	0,15	2,61200	6-2000-250-00/998
280	287,00	0,80	287	0,50	0,15	2,92300	6-2000-280-00/998
300	307,00	0,80	307	0,50	0,15	3,13000	6-2000-300-00/998
350	357,00	0,80	357	0,50	0,15	3,64800	6-2000-350-00/998