


VACUFLEX® VSM-SO1

Very smooth inside profile hose made of modified TPO

- Applications** vacuum cleaner, industrial vacuum cleaners, cleaning, dust extraction, sprayers
- Structure** TPO, black / grey aluminium (similar RAL 9007), profile helix / solid profile helix
- Temperature** -50°C up to 60°C
- Properties** excellent flexibility, crush-resistant, can be driven over, very good chemical resistance, good flexibility restoring force after compression or bending



Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
25	33,00	50	0,60	0,60	0,15030	4-1125-025-00
27	35,50	60	0,60	0,60	0,17040	4-1125-027-00
29	38,50	65	0,60	0,60	0,18270	4-1125-029-00
32	40,50	70	0,50	0,50	0,32700	4-1125-032-00
32	40,50	70	0,50	0,50	0,22900	4-1125-032-01
36	44,70	75	0,50	0,50	0,28907	4-1125-036-00
37	45,10	80	0,50	0,50	0,29500	4-1125-037-00
38	48,00	80	0,40	0,40	0,36230	4-1125-038-00
40	50,00	90	0,40	0,40	0,38140	4-1125-040-00
50	61,00	120	0,25	0,25	0,51630	4-1125-050-00
60	72,00	140	0,20	0,20	0,62660	4-1125-060-00
63	75,00	148	0,19	0,19	0,65457	4-1125-063-00
70	80,00	165	0,17	0,17	0,69000	4-1125-070-00
75	87,00	180	0,16	0,16	0,74000	4-1125-075-00
80	92,00	200	0,15	0,15	0,79000	4-1125-080-00